



- Available in mesh size & material to your specification.
- Wire mesh overlays (Inside or Outside) available upon request.
- Tag numbers, size & rating stamped on handle as standard.
- Available as either short (S) or long (L) version.

All data subject to confirmation at time of order. Our policy is one of continuous improvement and we reserve the right to amend any details without prior notice.

Technical Data

| MODEL/ASSEMBLY NUMBER | SIZE NB | DIMENSIONS (mm) | | | | | WEIGHT (kg) | |
|-----------------------|-------------|-----------------|------|-----|-----|---|-------------|------|
| | | A | | B | C | D | S* | L* |
| | | S* | L* | | | | | |
| A050/R90/316/TW* | 50mm (2") | 114 | 152 | 44 | 138 | 3 | 0.2 | 0.3 |
| A080/R90/316/TW* | 80mm (3") | 165 | 228 | 67 | 163 | 3 | 0.4 | 0.4 |
| A100/R90/316/TW* | 100mm (4") | 215 | 292 | 88 | 201 | 3 | 0.6 | 0.7 |
| A125/R90/316/TW* | 125mm (5") | 266 | 355 | 117 | 242 | 3 | 0.7 | 0.9 |
| A150/R90/316/TW* | 150mm (6") | 330 | 431 | 139 | 284 | 3 | 1.1 | 1.5 |
| A200/R90/316/TW* | 200mm (8") | 431 | 584 | 181 | 354 | 3 | 2.0 | 2.7 |
| A250/R90/316/TW* | 250mm (10") | 533 | 685 | 228 | 430 | 5 | 2.7 | 3.4 |
| A300/R90/316/TW* | 300mm (12") | 635 | 825 | 276 | 493 | 5 | 3.6 | 4.9 |
| A350/R90/316/TW* | 350mm (14") | 660 | 889 | 320 | 516 | 5 | 4.5 | 5.4 |
| A400/R90/316/TW* | 400mm (16") | 749 | 990 | 368 | 570 | 5 | 5.4 | 7.2 |
| A450/R90/316/TW* | 450mm (18") | 838 | 1117 | 415 | 633 | 5 | 6.8 | 9.5 |
| A500/R90/316/TW* | 500mm (20") | 939 | 1244 | 466 | 693 | 5 | 9.0 | 11.7 |
| A600/R90/316/TW* | 600mm (24") | 1117 | 1473 | 568 | 833 | 5 | 12.2 | 16.3 |

* 'S' Denotes Short (150% Open Area) & 'L' Denotes Long (200% Open Area)

Materials

| ITEM No | DESCRIPTION | MATERIAL |
|---------|------------------|--------------------|
| 01 | SUPPORT RING | AISI 316 (~1.4404) |
| 02 | HANDLE | AISI 316 (~1.4404) |
| 03 | PERFORATED PLATE | AISI 316 (~1.4404) |
| 04 | MESH LINING | AISI 316 (~1.4404) |

Comment:

The Witch-Hat strainer has to be used for temporary applications only - e.g. for commission of the plant but not for continuous operation. For permanent operation stronger versions are available optionally.